

AMBRA S -en- RECESSED LUMINAIRES Ø 135

Adjustable recessed downlight. Die-cast aluminium body, metallized polycarbonate reflector. Body and ring white color + glossy chrome reflector. Interchangeable reflectors to obtain different shades of light.

20/40/55 ° beam. Diameter of 135mm, hole of 118mm, height 95mm. Led from 12w to 17w. Availability of LED CRI> 90 and fashion and art LED with CRI> 98. Ugr <19.




IP20

RG1



DATA SHEET



CHARACTERISTICS

LED modules: Latest generation COB Led. Other configurations available on request.

CRI 98 A+ ART

W	K	lm	mA	CRI
12	3000	1305	350	98
17	3000	1820	500	98

CRI >90 A+ FASHION

W	K	lm	mA	CRI
12	3250	1380	350	>90
17	3250	1925	500	>90

AMBRA S -en- RECESSED LUMINAIRES ○ ○98

CRI >90 A+

W	K	lm	mA	CRI
12	2700	1315	350	>90
12	3000	1380	350	>90
12	4000	1450	350	>90
17	2700	1820	500	>90
17	3000	1915	500	>90
17	4000	2015	500	>90

CRI >80 A++

W	K	lm	mA	CRI
12	2700	1535	350	>80
12	3000	1610	350	>80
12	4000	1690	350	>80
17	2700	2125	500	>80
17	3000	2230	500	>80
17	4000	2340	500	>80

NOTES AND ACCESSORIES

Honeycomb grid.
 Compensation ring.
 Box for concrete.
 Emergency kit SA: 1 hour @350mA.
 20°, 40°, 55° beam.
 Availability of standard, dimmable, Dali dimmable and CASAMBI Dali driver.
 Luminaires not suitable for covering with thermally insulating material.

Last update: 31 October 2018