

## ARA 56 S/L -en- SUSPENSIONS Ø 56

Suspended luminair. Extruded aluminium body, diffuser with 24/38° polycarbonate lens or 60° aluminium reflector. With a diameter of 56mm and a height of 245mm. Led 12w.

Possibility to choose among a wide selection of RAL colours: grey ral9006, white ral 9016, black ral9005, red ral3001, orange ral2004, yellow ral1021, green ral6029, metal blue ral5026.

As regards the galvanic treatments finish, the proposal is: gold 24K, gold 24K frosted, chrome, chrome frosted, chrome black, bronze brass base, bronze copper base, brass, copper.



IP20 RG1 CE

### DATA SHEET



### CHARACTERISTICS

LED modules: Latest generation COB Led. Other configurations available on request.

CRI >80 A++

W	K	lm	mA	CRI
12	2700	1420	350	>80
12	3000	1500	350	>80
12	4000	1570	350	>80

## ARA 56 S/L -en- SUSPENSIONS Ø 87

### CRI >90 A+

W	K	lm	mA	CRI
12	2700	1220	350	>90
12	3000	1280	350	>90
12	4000	1350	350	>90

### CRI >90 A+ FASHION

W	K	lm	mA	CRI
12	3250	1380	350	>90

### CRI >90 A+ ART

W	K	lm	mA	CRI
12	3000	1310	350	98

## NOTES AND ACCESSORIES

Opal diffuser.  
Honeycomb grid.  
Mechanical/electrical adapter 6° for track available.  
Emergency kit SA: 1 hour @350mA with remote application.  
Beam with 24°, 38° polycarbonate lens or 60° aluminium reflector.  
Standard driver included, Dali dimmable driver on request.

Last update: 3 November 2018