

ARA 85 S/L -en- SUSPENSIONS O O89

Suspended luminair. Extruded aluminium body, diffuser with 12/24/38° polycarbonate lens or 60° aluminium reflector. With a diameter of 85mm and a height of 245mm. Led 17w.

Possibility to choose among a wide selection of RAL colours: grey ral9006, white ral 9016, black ral9005, red ral3001, orange ral2004, yellow ral1021, green ral6029, metal blue ral5026.

As regards the galvanic treatments finish, the proposal is: gold 24K, gold 24K frosted, chrome, chrome frosted, chrome black, bronze brass base, bronze copper base, brass, copper.



IP20

RG1



DATA SHEET



CHARACTERISTICS

LED modules: Latest generation COB Led. Other configurations available on request.

CRI >80 A++

W	K	lm	mA	CRI
17	2700	2410	500	>80
17	3000	2475	500	>80
17	4000	2580	500	>80

ARA 85 S/L -en- SUSPENSIONS Ø 089

CRI >90 A+

W	K	lm	mA	CRI
17	2700	2045	500	>90
17	3000	2100	500	>90
17	4000	2250	500	>90

CRI >90 A+ FASHION

W	K	lm	mA	CRI
17	3250	1930	500	>90

CRI >90 A+ ART

W	K	lm	mA	CRI
17	3000	1820	500	>90

NOTES AND ACCESSORIES

Opal diffuser.
 Honeycomb grid.
 Mechanical/electrical adapter 6° for track available.
 Emergency kit SA: 1 hour @350mA with remote application.
 Beam with 12°, 24°, 38° polycarbonate lens or 60° aluminium reflector.
 Standard driver included, Dali dimmable driver on request.

Last update: 3 November 2018